# **Metor 200 HDe**

Walk-Through Metal Detector High Discrimination

**PEOPLE SCREENING** 

**High Efficiency Screening** 

**Non-Compromising Detection** 

**Excellent Discrimination** 

**Unique Multi-Zone Principle** 

### HIGH EFFICIENCY SCREENING

The **Metor 200 HDe** High Discrimination walk-through metal detector is specifically designed for demanding, high traffic screening applications. It detects weapons efficiently and discriminates against harmless personal objects. Therefore, traffic flow can be maintained at an optimum rate in locations where fast throughput is essential.

### **UNIFORM DETECTION**

The sensitivity of the entire metal detector and individual zones can be easily adjusted. This flexibility allows the Metor 200 HDe to operate in difficult environments. It performs optimally even in locations where external stationary metal impairs the detection uniformity of conventional metal detectors. For example, when a Metor must be used in proximity to large metal objects, its multi-zone structure enables detection uniformity to be easily restored. Ambient electromagnetic interference can be measured to optimize the unit's performance.

### **UNIQUE MULTI-ZONE PRINCIPLE**

True multi-zone design guarantees first-rate performance. Each detection zone functions as an independent detector and automatically increases discrimination by reducing the cumulative signal effect caused by distributed harmless objects.

### THE BENEFITS OF THE MULTI-ZONE PRINCIPLE

- Superior discrimination.
- · Reliable detection of threat items.
- High traffic throughput.
- Optimum immunity to environmental interference and external stationary metal.

### **MOBILITY**

The unit can be easily moved to different locations.

### **ZONE DISPLAY**

The zone display identifies the level(s) at which detected object(s) are carried. This enables security personnel to immediately target objects and ensure that maximum throughput can be maintained in high traffic locations.

### STATISTICS


Intelligent traffic and alarm counters calculate the traffic flow and alarm rates. The counters can be set to increment and decrement, thereby giving a true traffic count. By using the MetorNet Remote Security Monitoring System, it is easy to collect statistics while controlling and monitoring multiple Metor brand walk-through metal detectors.





An OSI Systems Company

# EIGHT INDEPENDENT DETECTION ZONES



- Target objects are independently detected in each zone.
- Signals from distributed harmless objects do not combine to produce unnecessary alarms.
- Provides more uniform detection.
- Zone display illuminates at the level where a detection occurs.

### **Options & Accessories**

### **REMOTE ZONE DISPLAY UNIT:**

Remote zone display unit can operate at a distance of up to 65 m (213 ft) from the detector. It shows the position of detected items and generates an audible alarm.

**BATTERY BACKUP:** For 2-hour runtime when no power is available.

**CARRYING BAG:** Ideal for transportation and/or storage.

**WHEEL KITS:** For easy mobility of the metal detector in an upright position.

**TEST PIECES:** To assist in calibration and testing.

METORNET 3 PRO: Remote Security Management System collects the statistics on traffic flows and alarm data of up to 255 Metor Walk-Through Metal Detectors and generates easy-to-read reports. It allows detector security levels to be changed from a central PC.

### **Standard Accessories**

PROTECTIVE BOOTS: ABS-plastic boot protects coil panels from floor washing liquids and scuffmarks. The boot is easy to install and change. It will have no effect on the usability of the floor-level zone display.



An OSI Systems Company

# Metor 200 HDe

Walk-Through Metal Detector

## **OPTIONAL ACCESSORIES**

#### **PEOPLE SCREENING**







### **BATTERY BACKUP**

### **CARRYING BAG**

### REMOTE ZONE DISPLAY UNIT

### **CUSTOMER SUPPORT**

Our team is dedicated to providing a prompt, effective and personalized response that exceeds your expectations. With spare parts inventory and skilled technicians all over the world, you can be certain Rapiscan Systems will always be prepared with a solution to address your requirements. By measuring response time, parts delivery and support status, our team embraces a customer focused philosophy to ensure continual improvement in customer support, products and services.

<b>CONFORMITY</b> Rapiscan Systems Metor brand of walk-through metal detectors conform to the applicable EU directives and meets the requirements of the following standards:					
Safety Standards	EN 60950 (Electrical safety)				
EMC Standards	EN 50081-1 (Emission), EN 50082-1 (Immunity)				
Other Standards	NILECJ-0601, security levels 1-5 (covers the design and performance of walk-through metal detectors), TSA approved and DfT (UK) approved. Safe for wearers of heart pacemakers, pregnant women and magnetic recording materials.				
<b>C</b> € Compliant	Yes				
SPECIFICATIONS					
Ambient Operating Temperature	From -10 C to +55 C (+ 14 F to +131 F)				
Humidity	Up to 95%, no condensation				

Humidity	00 10 0070, 110 0011		
Protection	IP 20 (EN 60529)		
Power Supply	AC Power: 90-264		

wer: 90-264VAC/45-65Hz Battery: 24-35V DC Consumption: 45W Fuse: T1A 5x20 mm Power cord length: 2.5 m (8.2 ft)

Audible and visible alarm. **Alarm** Alphanumeric display and zone display. Relay contact for remote alarm (SPDT) 100 sensitivity steps per program Sensitivity

All eight zones are individually adjustable (0 to 255 %) with respect to the overall sensitivity level **Zone Sensitivity** Adjustment Automatic or manually set. Calibration

An automatic sensitivity function selects the appropriate sensitivity for a specific weapon or test object. This eliminates the time consuming trial and error method.

Reset Time	Adjustable
Interference	Digital filtering by signal processor and user selectable frequency selection

Suppression User-friendly diagnostics identify fault condition **Advanced Self-**

**Adjusting Diagnostics** Two (2) years, parts and labor Warranty

MetorNet Remote Security Monitoring System compatible (RS422 and Ethernet) **Network Connections** 

85.7		78.4		
	30 in.	. (760 r	nm)	

→ 36.2 in. (920 mm) →

ISO 9001:2000 Certified

**APPLICATIONS** 

Airports **Public Buildings** Conferences

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice.

23 4 in (594mm)

## www.rapiscansystems.com • sales@rapiscansystems.com

### AMERICAS, CARIBBEAN 2805 Columbia Street

Torrance, California 90503 UNITED STATES of AMERICA Tel: +1 310-978-1457

Fax: +1 310-349-2491

### **EUROPE, MIDDLE EAST, AFRICA**

X-Ray House Bonehurst Road Salfords Surrey RH1 5GG UNITED KINGDOM

Tel: +44 (0) 870-7774301 Fax: +44 (0) 870-7774302

### ASIA

240 Macpherson Road #07-03 Pines Industrial Building Singapore 348574 SINGAPORE

Tel: +65-6743-9913 Fax: +65-6743-9915

### AUSTRALIA

Rapiscan House 4 Ross Street South Melbourne Victoria Australia 3205

AUSTRALIA Tel: +61 3 9929 4600 Fax: +61 3 9929 4655